


FINE CLEANER DELTA 117

Designed for high quality fine cleaning of seeds, malting barley, legumes and grain.

The Delta 117 fine cleaner include shaker feeder, pre-suction and after-suction system, electronic control system and flexible screen flow.





PERFORMANCE

Materials	Bulk density t/m³	Moisture content %	Capacity t/h
Barley	0.68	14 (15)	15 (25)
Clover	0.82	14 (15)	6
Coffee, green	0.65	14 (15)	16 (16)
Maize	0.71	14 (15)	8–15 (20)
Oats	0.51	14 (15)	11 (16)
Peas, common	0.7	14 (15)	12–14 (15–18)
Rapeseed	0.74	7–9	10 (16)
Rice, paddy	0.51	14 (15)	6-8.5 (10-12)
Rice, white	0.75	14 (15)	16 (25)
Rye	0.69	14 (15)	15 (20–30)
Ryegrass	0.3	14 (15)	2.5
Sorghum	0.64	14 (15)	15 (25)
Soybeans	0.72	14 (15)	12-14 (15-18)
Sunflower	0.4	7–9	5–8 (8)
Wheat	0.76	14 (15)	16 (20–30)
			0.1

Legend: Values in parentheses are for industrial cleaning. Other values are for fine cleaning.

Note: Capacities may vary for different impurity and moisture contents.

SCREENS

Screen angle 5° Screen area, total 18 m^2

Screen size 1 250×800 mm (18 pcs)

DIMENSIONS

Overall length 3 789 mm
Overall height 3 096 mm
Overall width 1 875 mm

WEIGHT

Weight, empty 3 160 kg Weight, operating (wheat) 3 490 kg Weight, choked (wheat) 7 790 kg

OPERATING SPEED

Shaker feeder (shaft) 140–700 rpm Screens (shaft), fixed speed 280–285 rpm Screens (shaft), variable speed 260–320 rpm

ELECTRICAL RATINGS

Motor, shaker feeder 0.75 kW Motor, screens 2.2 kW Control panel 110–230 V

AIR SUPPLY AND EXTRACTION

Aspiration volume 11 000 m³/h

DYNAMIC LOADS

NOISE

Sound pressure level, empty 81.6 dB(A) Sound power level, empty 96.1 dB(A)

COMPLIANCE

EU machinery legislation Yes
EU ATEX legislation Option*
EU food contact legislation Option*
* Consult your Cimbria dealer for full details.

ENVIRONMENTAL CONDITIONS

Environment Indoors

Temperature From -20°C to +40°C

Altitude Up to 800 m

SURFACE PROTECTION

Frame and enclosure Paint (corrosivity category

C2; low durability)

LIFETIME

Intended life limit 20 years

