

# CENTRICOATER CC150

The CC150 is a fully automatized Centricoater for operating within a seed line. The operator sets all necessary parameters on the touch display, eg. weight, speed of drives, amount and timing of dosing the slurries, etc. After starting the Centricoater, the seed is measured by the built-in scale, using electronic load cells. Dumping the pre-scaled seed into the mixing drum is done automatically. The dosing of the different slurries is done according to the setup of the operator. A PLC controls the heart of the process, the coating of the seed. This guarantees reproducible conditions and quality for each batch.

The whole machine is ready-prepared for operation, only the power supply must be wired to the local main electric panel, and connection of the pneumatic air supply. A spout for connecting the existing aspirating system is also prepared on the CC150, the aspirating system must be provided locally. The slurry dosing lines will be connected with the pump by means of flexible hoses.



## Standard components (for liquid coating):

- self-supporting all-steel construction, consisting of:
  - scale with electronic loadcells, accuracy +/- 0.25 % referred to max. weight
  - mixing drum using the Centricoater-principle
  - with the dosing systems described below
  - possible to add future upgrades
- electric switchboard on main frame, completed and ready, consisting of:
  - the touch display for setting the parameters for weighing and coating process
  - the PLC for operating the coating process
  - the controller for the scale
  - incl. fuses, circuit breakers, motor protection switches, etc.
  - rotor drive operated by frequency inverter
  - possibility for connecting external seed level sensor for the scale's pre-bin and silo below
  - possibility for connecting external slurry level sensor
  - possibility for operating an (optional) sampletaker
  - GSM LAN modem for remote maintenance

Mixing drum	
Mixing drum size (referred to wheat)	150 kg
<b>Recipes:</b> (values can differ depending on type of seed and quantity of slurry)	
Capacity (referred to wheat)	max. 15 t/h
Dosing of slurries within	10 .. 20 s
Mixing after dosing within	10 .. 15 s
Discharging seed within	5 .. 10 s
<b>Power supply: (standard)</b>	
Main power supply appr. 25 kW	3/N/PE 400V 50 Hz min. 63A
<b>Air volume</b>	
Air requirements	500 m <sup>3</sup> /h @dP 1,5 kPa
<b>Pneumatic</b>	
Requirements	4 Nm <sup>3</sup> /h, 6 bar nom.
<b>Equipment</b>	
Beltfeeder for scale	optional
Slideable scale	optional
Glass cylinder	1,5 l
Pump D25	60 .. 500 l/h
Powder feeder	Ø60 mm
<b>Dimensions</b>	
Length	2200 mm
Width (without PD)	1900 mm
Height (standard)	3000 mm
<b>Total weight</b>	
Net	3000 kg

Technical data can vary for certain of the above due to continued development or a different machine composition.