

Data Sheet 23.2

Two-way Valves Type Q-24



Two-way valves

Two-way valves type LM and LN can be used for diverting the grain flow. Type LM valves are used where a vertical spout divides into two sloping spouts while type LN delivers the grain in a sloping and a vertical spout.

For manual operation of the two-way valves a handle/lever is used, this can be mounted on the side of the valve in the position that is most convenient for the particular location. The actual position of the shutter is shown by

means of an arrow pointing in the direction of the grain flow. This device can be replaced by an electrical indicator showing flow direction by means of signal lights which, if required can be fitted after installation. Manually operated two-way valves type LN are supplied with shutter regulation on both side.

Additionally the two-way valves can be delivered pneumatically operated enabling a number of valves to be easily controlled from a remote control panel.

38°

240 outside, 240 outside, 192, 22, 125, 189, 41, 24, XY 13, XY11-1

Manually	Manually w. indication	Pneumatically	Motorised w. indication
LM72	LM74	LM78	LM79

55°

240 outside, 240 outside, 233, 47, 208, 137, 44, 196, 37, XY 13, XY 11-1

Manually	Manually w. indication	Pneumatically	Motorised w. indication
LM752	LM754	LM755	LM759

38°

240 outside, 240 outside, 312, 34, 185, 190, 56, 21, 148, 44, 396, XY 12, XY11-1

Manually	Manually w. indication	Pneumatically	Motorised w. indication
LN72	LN74	LN78	LN79

55°

240 outside, 240 outside, 357, 36, 319, 138, 95, 12, 197, 40, 468

Manually	Manually w. indication	Pneumatically	Motorised w. indication
LN752	LN754	LN755	LN759

LN72 and LN74 can be mounted from both side.

The shown handles have to be ordered separately.

Copyright © - The right to alterations is reserved

